



CONNECTION RATIO AT LIMITED CONDITIONS >130%

ONLY following indoors connected to :

RXYQ 5 ~ 54P



small duct

FXDQ-M



small duct

FXDQ-N



standard duct

FXSQ-M



wall mounted

FXAQ-M


Total indoor
index
50 ~ 200 %
index of outdoor

CONNECTION RATIO AT LIMITED CONDITIONS >130%

R-410A

Use of following indoors connected to :


RXYQ 5 ~ 18P



small duct **FXDQ20-25M**



small duct **FXDQ20-63N**



standard duct **FXSQ20-125M**



wall mounted **FXAQ20-63M**



2 blow **FXCQ20-125M**



600*600 **FXZQ20-63M**



corner **FXKQ32-63**



ceiling susp. **FXHQ32-125M**



high esp duct **FXMQ40-250M**



floor standing **FXLQ20-63M**



conceiled floor **FXNQ20-63M**



4blow concealed **FXUQ71-125M**



4 blow **FXFQ32-125M**

200 %



CONNECTION RATIO AT LIMITED CONDITIONS >130%

Use of following indoors connected to :

RXYQ 20 ~ 36P



small duct **FXDQ20-25M**



small duct **FXDQ20-63N**



standard duct **FXSQ20-125M**



wall mounted **FXAQ20-63M**



2 blow **FXCQ20-125M**



600*600 **FXZQ20-63M**




corner **FXKQ32-63**



ceiling susp. **FXHQ32-125M**



high esp duct **FXMQ40-250M**



floor standing **FXLQ20-63M**



conceiled floor **FXNQ20-63M**



4blow concealed **FXUQ71-125M**



4 blow **FXFQ32-125M**

160 %

CONNECTION RATIO AT LIMITED CONDITIONS ≤130%

Use of following indoors connected to :

RXYQ 34 ~ 54P

130 %

	small duct	FXDQ20-25M
	small duct	FXDQ20-63N
	standard duct	FXSQ20-125M
	wall mounted	FXAQ20-63M
	2 blow	FXCQ20-125M
	600*600	FXZQ20-63M
	corner	FXKQ32-63
	ceiling susp.	FXHQ32-125M
	high esp duct	FXMQ40-250M
	floor standing	FXLQ20-63M
	conceiled floor	FXNQ20-63M
	4blow concealed	FXUQ71-125M
	4 blow	FXFQ25-125M

CONNECTION RATIO AT LIMITED CONDITIONS $\leq 130\%$

R-410A

Use of ANY following indoors connected to : RXYQ 5 ~ 48P



4 blow FXFQ20 , 25M

130 %



HRV+DEX VKM 50 , 80 , 100G